



Huslån Vårgårdahus®

# WINDOW AWNING

## DA42 & 45


A sturdy awning with drop arms, constructed to suit most buildings, for example private houses, shops, offices, schools and hospitals. DA42 and 45 are perfect for motorisation and therefore very suitable for large motorised facilities. Aluminium cassette protects the fabric against rain and dirt.




# WINDOW AWNINGS DA42 & 45

DIMENSIONS (m)	DA42	DA45
Arm projection	0,5-1,0	0,6-1,4
Max width	5,0	7,0
Serie connection with motor	20,0	20,0
Wind class	3	3

According to EN13561



Arm bracket DA42



Arm bracket DA45



Standard front profile.



Designed front profile.



Standard colours

## Operation

Exterior or interior operation with polyester tape is standard. Optionally, operation can be made with crank or motor. The motor can be supplemented by automation, ie remote control or sun and wind automation.

## Mounting

The awning can easily be mounted directly into the window-sills, on the wall or in a corniche. If needed, adjustable brackets can be mounted to adjust the awning into the window sills in depth by 45–185 mm.

## Drop arms

The arms are produced in extruded aluminium and the arm components in diecast zinc. For the best fabric tension, our drop arms have adjustable springs. Wind secured drop arms are recommended if the awning is exposed to strong winds.

## Awning Fabric

Choose from a wide collection of both plain and striped fabrics.

## Awning Hardware

The awning hardware with details can be ordered in 3 standard colours: White, Grey and structured Black. With longer delivery time, any RAL colour is available.

