




# WINDOW AWNING

## DA22 & DA32

DA22 and DA32 are modern, compact and stylish awnings to suit most buildings. DA32 is fitted with an elegant aluminium cassette to protect the fabric against rain and dirt. The drop arms have adjustable springs for correct fabric tension. Indoor or outdoor operation with polyester tape with the extra option to motorise the awning.

# WINDOW AWNINGS DA22 & DA32



DA22 without cassette.



The DA32 awning is equipped with an aluminium cassette to protect against rain and dirt.



Standard colours



Standard front profile.



Designed front profile.

## DIMENSIONS (m)

Arm projection	0,5-1,0
Max width	3,2 per unit
Series connection	10,0 with motor
Wind class	3

According to EN13561

## DA22

A drop arm awning without cassette.

## DA32

A drop arm awning with cassette.

## Operation

Indoor or outdoor operation with polyester tape is standard. To store and protect the tape, the awning can easily be supplemented by a tape collector.

Optionally, operation can be made with crank or motor. The motor can be supplemented by automation, ie remote control or sun and wind automation.

## Mounting

The awning can easily be mounted directly into the window-sills, on the wall or in a corniche. If needed, adjustable brackets can be mounted to adjust the awning into the window sills in depth by 45–185 mm.

## Drop arms

The arms are produced in extruded aluminium and the arm components in diecast zinc. For the best fabric tension, our drop arms have adjustable springs.

Wind secured drop arms are recommended if the awning is exposed to strong winds.

## Awning fabric

Choose from a wide collection of both plain and striped fabrics.

## Awning Hardware

The awning hardware with details can be ordered in 3 standard colours: White, Grey and structured Black. With longer delivery time, any RAL colour is available.

